

Switch 19" 16 & 24 port 10/100/1000



Switch 16 & 24 portar 19" 10/100/1000 Mbps.

16 och 24 portars 19" switch 10/100/1000 Mbps. För montage i stativ/skåp, hållare för 19" montage medföljer, även stackbar. Stödjer Auto MDI/MDIX och store-and-forward, Quality of Service funktion, plug and play. Uppfyller IEEE802.3, IEEE802.3u, IEEE802.3ab. Mått: 437x 177x 43mm

Teknisk information:

Main features:

Simple solution for expanding your networking, idea for VOIP and games. Space saving design and easy to install and use. High speed and excellent performance
Complies with IEEE 802.3x full-duplex and flow control
16 or 24 10/100/1000Mbps ports connect to the workstation
Supports Auto MDI/MDIX
Supports NWA auto-negotiation function, auto-detect transfer data rate, UPnP, full-duplex, and automatically chooses the best network connectivity mode
Supports IEEE802.3x full-duplex flow control, and half-duplex backpressure flow control
2 years warranty

Protocol and standards:

IEEE802.3, IEEE802.3u and IEEE802.3ab

Interface:

16 or 24 10/100/1000Mbps RJ45 Ports

Power supply:

AC 110-240V 50/60Hz input

Mac address table size:

8K

Packet buffer:

2Mb

Backplane bandwidth:

32Gbps

Transmission method:

Store-and-Forward

Transmission media:

10Base-T Cat.3 or 3e UTP
100Base-TX Cat.5 UTP
1000Base-T Cat.5e UTP

Operating temperature:

0 to 40°C

Operating humidity:

10 to 90% Non condensing

Storage temperature:

-40 to 70°C

Storage humidity:

5 to 90% Non condensing

Dimensions

177 x 437 x 43 mm

Housing material:

Metal

Gross weight:

2.53 Kg

Certificate:

CE, RoHS

Warranty:

24 months

E-nummer

Typ

Benämning

Antal/fp

51 870 76

GGM GS1600

Switch 16P 10/100/1000 19"

1 st

51 870 78

GGM GES2400

Switch 24P 10/100/1000 19"

1 st