



**Category 6A RJ45 molded with latch protector patch cord UTP AWG28/7 10G
ISO/IEC Class EA, ANSI/TIA-568.2-D, LSOH IEC 60332-1
Overall diameter: 4,8mm, length 30 cm - 10 m, white**

GGM CAT6AxxMHFW



With each GIGAMEDIA CAT6A patch cord we are performing electrical testing and are able to support 10 Gigabit applications. The 100% copper conductors and optimal electrical performance ensure perfect compatibility with power over Ethernet technologies (PoE, PoE+, 4PPoE). During assembly, the best connection and control technologies are implemented to guarantee reliability and performance.

- Category 6A U/UTP unshielded
- Stranded plain anneal bare copper wire, 28/7AWG
- Standards:
 - ANSI/TIA/EIA-568.2-D,
 - EN 50173-1, EN 50173-2 et EN 50173-5
 - ISO/IEC 24764
 - IEC 61935-2
- Applications :
 - IEEE 802.3 : 10Base-T ; 100Base-T ; 1000Base-T et 10Gbit Ethernet
 - IEEE 802.3at/af (PoE/PoE+)
- Frequency range: from 0 to 550 MHz
- Characteristic impedance: 100 Ohm
- Outer jacket : LSZH IEC 60332-1
- Overall Diameter : 4,8 mm
- Over molded slim boots with latch protector
- Available colors : White RAL9010