



19" CABLING FLOOR STANDING CABINET IPRACK GGM IP4288N



42 U
800 X 800 mm
Grey

Specially designed to meet (according to their classification) the requirements required within some premises (Ex : Industry, warehouse, car park, ...).

The IPRACK is characterized by the level of sealing it provides against dust and against water jets from all directions at the lance, according to the IEC 60529 standard.

A product of very high quality, both in terms of design and finish, it will meet the most stringent requirements.

Other dimensions and configurations possible, please contact us.

Type :	Cabling
Frame :	Galvanized steel, mechanically screwed (fully removable)
Mounting profiles :	Four 19" mounting profiles adjustable in depth (zinc plated), "U" markings, 9.5 x 9.5 mm perforations
Front door :	Reversible security front glass door with frame, can be opened up to 150°, locked by using multipoint swing handle with key lock (N°333)
Rear door :	Reversible full metal door, can be opened up to 150°, locked by using multipoint swing handle with key lock (N°333)
Side panels :	Removable, locked by using screws to the frame
Roof :	Full metal plate
Base :	Full, with 3 removable partial shutter plates
Ground contact :	100 mm plinth
Colour :	Grey
Paint feature :	Doors, panels and top sheet are coated with epoxy-polyester paint
Gaskets feature :	All gaskets are in hot-cast polyurethane
Protection (IP) :	55
Load capacity :	1300 kg
Earthing kit included :	Yes

RÉFÉRENCE	DESCRIPTION
GGM IP4288N	19" Cabling floor standing cabinet IPRACK 42U 800 X 800 mm - Grey